

## MICRON CARTRIDGE FILTERS

The EnviCF cartridge is constructed of thermally bonded polypropylene microfibres to ensure high efficiency. The filter incorporates a rigid polypropylene centre core for increased collapse strength and durability. This thermal bonded micro-fibre construction has minimal fibre release, consistent flow rate and superior filtration performance. It is also not brittle or prone to breakage problems like resin-bonded cartridges. Unique micro-grooves provide added surface area. The recommended temperature limit of 40° F to 175° F allows it to be used in many hot water applications.

## **FEATURES**

- Free of surfactants, binders and adhesives
- Excellent flow with low pressure drop
- · High dirt holding capacity
- 100 % Polypropylene for wide chemical compatibility
- High strength & pressure resistance
- Will not impart taste, odour or colour to the liquid being filtered
- One piece construction up to 1016 mm & more
- Nominal & absolute filtration rating NSF42 and FDA CFR title 21 certified cartridges are available

## **APPLICATIONS**

- Water treatment: Membrane protection, resin tap
- Food & Beverages: Bottled water, flavours, polishing lines
- Pharmaceuticals: Base product clarifications, membrane pre-filter
- Fine chemicals: Solvents, process streams, water purification
- Magnetic coating: Dispersions, coating lines, solvents
- **Petrochemicals:** Water flood, completion fluids, amines **Cosmetics:** Alcohols, essential oils , water lines
- Metal finishing: Plating solution, paint and resin products, wash
- Electronics: Electroplating, etching, image development

TYPE	MICRON RATING	CARTRIDGE DIAMETER	CARTRIDGE LENGTH
Spun (S)	1	2.5" (XS)	10"
Wound (W)	5	4" (XL)	20"
	10		30"
	20		40"
	50		50"
	100		60"

MODEL SELECTION
Model number for EnviCF Cartridge of Spun type with micron rating of 5, diameter of 4" and length of 20" would be
EnviCFS5-XL-20



SPUN FILTER CARTRIDGE



WOUND FILTER CARTRIDGE

## **HEAD OFFICE:**

Arvind Envisol Ltd. Arvind Mill Premises, Naroda Road, Ahmedabad - 380025, India. Toll Free No.: 1800 843 9988 • Email: sales@envisol.co.in